

Select Sound Module (SSM)



DESCRIPTION

Normally used for auxiliary and/or remote alarm annunciation, the Select Sound Module (SSM) is able to create two distinct, audible alarms: A general alarm and/or an urgent alarm. Using DIP switches inside the unit, the two active tones are programmed from a selection of 8 tones in each group. The unit also accepts a control signal from an external auxiliary Form C relay or switch, which will lower the volume by 50% (night usage). The SSM is a solid-state device with a miniature speaker and is designed to be mounted in a standard single gang electrical box.

FEATURES

- Flush mounts to standard single gang electrical box mount
- Day/Night volume control input (12V active high input for reduced night volume)
- 16 possible sounds: 8 pleasant tones for general alarms and 8 brisk tones for urgent alarms
- Field-adjustable volume setting using a volume control (screwdriver required)
- General and Urgent alarms will alternate if both are activated
- Reverse polarity protection
- Bakelite plastic cover with ivory finish



SPECIFICATIONS

Order Information

Model	Select Sound Module
Part Number	AGESM01-016

General

Input Voltage	12 - 24 VDC
Other Current Draw	100 mA

Additional Inputs/Outputs

Audio Output Level	75 dBA @ 1M day 35 dBA @ 1M night
Output Tones	8 general and 8 urgent
Level Control	Day/Night operation

Physical

Size	4.5" x 3.0" x 1.5" (11.4 x 7.6 x 3.8 cm)
Mounting	Single gang box
Max power cable length (18A WG)	328 ft. (100 M)
Max signal cable length (22A WG)	328 ft. (100 M)

Warranty

2 years